

DİJİTAL ŞİFRELİ KASALAR

DIJITAL COMBINATION SAFE



KE060/30-100

TEKNİK ÖZELLİKLER | TECHNICAL SPECIFICATIONS

İç Ölçüler	427 x 302 x 192 mm (GxDxY)
Dış Ölçüler	430 x 350 x 195 mm (GxDxY)
Net/Brüt Ağırlık	10.6 KG
Enerji Beslemesi	4 adet AA alkaline pil
Çalışma Voltajı	DC 4.2V [±] 0.2V
Statik Akım	≤ 30uA
Dinamik Akım	≤ 400mA
Çalışma Sıcaklığı	0° C ~ 55° C
Çalışma Nem Oranı	20% ~ 93% ± 2RH

Internal Dimensions	427 x 302 x 192 mm (W x D x H)
Outside Dimensions	430 x 352 x 195 mm (W x D x H)
Net/Gross Weight	10.6 KG
Power Supply	4 AA alkaline batteries
Alarm Voltage	DC 4.2V [±] 0.2V
Static Current	≤ 30uA
Dynamic Current	≤ 400mA
Working Temperature	0° C ~ 55° C
Working Humidity	20% ~ 93% ± 2RH

GENEL ÖZELLİKLER | GENERAL SPECIFICATIONS

- 4-6 rakamlı tek kullanımlık şifre özelliği
- 6 rakamlı master şifre özelliği
- Mekanik anahtarla açılış
- Duvara ve/veya yere montaj
- Açılış kaydının harici El Terminali ile alınabilmesi
- 4 Adet 1,5V AA Alkali pil
- 4-6 digit single-use password feature
- 6 digit master password feature
- Mechanical key opening
- Wall and/or floor mounting
- Opening record can be recorded with an external handheld terminal
- 4 1.5V AA alkaline batteries

KULLANIM ŞEKİLLERİ | OPERATIONAL METHODS

- Tek kullanımlık şifre
- Master şifre ile
- Mekanik anahtar ile
- By one time code
- By master code
- By override mechanical lock

