

EV/OFİS TİPİ KASALAR

HOUSEHOLD / OFFICE SAFES

KK 190



Pil bittiğinde enerji
besleme ünitesi ile açılış
Starting with the power supply
unit when the battery runs out



Alternatif
Kilit Sistemi
Alternative Locking
System



KAPLAMA RENKLERİ COATING COLOURS

STANDART STANDARD



RAL 7015

OPSİYONEL OPTIONAL



RAL 9005



RAL 9010

KK 190

Teknik Özellikler Technical Specifications

Renk / Colour	Standart RAL 7015 / Standard RAL 7015
Kilit Sistemi / Lock System	Elektronik Şifreli (HQ) + Electronic Passcode (HQ)
Dış Ölçüler / External Dimensions	G: 32 x D: 28,5 x Y: 19 cm W: 32 x D: 28,5 x H: 19 cm
İç Ölçüler / Internal Dimensions	G: 31,7 x D: 21,3 x Y: 18,5 cm W: 31,7 x D: 21,3 x H: 18,5 cm
İç Hacim / Volume	12,9 L
Ağırlık / Weight	8 kg
Gövde Sac Kalınlığı / Body Sheet Thickness	1,5 mm
Kapak Sac Kalınlığı / Cover Sheet Thickness	5 mm
Kilit Milleri / Locking Bars	 20 mm çapında 2 adet kilitleme mili / 20 mm diameter 2 pcs locking bar

* Farklı kilit sistemleri için satış temsilcileri ile irtibata geçebilirsiniz.

You can get in touch with sales representatives for further information on a variety of lock systems.



GENEL ÖZELLİKLER

- 4-6 rakamlı şifre özelliği
- 3 kez yanlış şifre girilmesi durumunda belli bir süre kendini kilitleme özelliği
- Acil durumlarda enerji besleme ünitesi ile açılış
- Sesli düşük pil uyarısı
- Kasa iç taban kaplaması halıfleks
- Dışarıdan müdahale edilemeyen gizli menteşe
- Duvara ve/veya zemine montaj imkanı
- 2 yıl garanti

GENERAL SPECIFICATIONS

- 4-6 digit code
- Automatically gets locked after a certain amount of time due to the three failed passcode entries
- Can be unlocked with a power override battery box in emergency
- Low battery alarm beep
- Safe interior bases - fully carpeted
- Blind hinge that cannot be tempered from outside
- Assembled to walls and/or floors
- 2 year warranty